

## Technical Data Sheet

### G-CRANKZ COMFORT SCOOTER 4T 10W-30

#### Product Description

G-CRANKZ COMFORT SCOOTER 4T 10W-30 is a Semi Synthetic oil developed for modern 4-stroke gearless scooters with automatic transmission. It utilizes the latest technology to deliver exceptional performance. This oil is made from high-quality Viscosity Index Hydrocracked base stocks and contains a precisely designed additive system with a low friction modifier. It ensures excellent performance and a trouble-free ride.

#### Application



- G-CRANKZ COMFORT SCOOTER 4T 10W-30 is specially recommended for all types of 4-stroke modern gearless scooters manufactured by leading companies such as BAJAJ, HONDA, KINETIC, TVS, SUZUKI and YAMAHA.

#### Key Performance Benefits

- Maintains viscosity in both high and low-temperature conditions.
- Provides greater fuel efficiency by reducing friction.
- Protects the engine from wear and tear, thus reducing maintenance costs.
- Ensures smooth acceleration in city "stop-n-go" conditions.
- It supports lowering emissions to permitted levels.

#### Performance Standards

- API SN
- JASO MB

#### GOHIL LUBRICANT PVT. LTD.

139, 1st Floor, Adarsh Industrial Estate, Andheri Sahar Road, Chakala, Andheri (E),  
Mumbai - 400 099. For consumer complaints:  
email: support@g-crankz.com Phone :- 180 0309 0302

A product by **GOHIL** |

## Typical Characteristics

TYPICAL PROPERTIES	ASTM METHOD	TYPICAL VALUE
Appearance	VISUAL	Bright & Clear
Kinematic Viscosity @40°C, mm <sup>2</sup> /s, cSt	ASTM D445	60.3
Kinematic Viscosity @100°C, mm <sup>2</sup> /s, cSt	ASTM D445	9.5
Viscosity Index	ASTM D2270	140
Flash Point (COC), °C	ASTM D92	220
Pour Point, °C	ASTM D97	-36
Total Base Number, mg KOH/g	ISO 6619	6.5
Density @29.5°C, kg/m <sup>3</sup>	ASTM D1298	0.850

Properties referred above are typical only and minor variations, which do not affect product performance, are expected to appear in standard manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade.

## Storage

To ensure product quality and safety, follow these storage guidelines:

- Store packages under cover to protect from the elements.
- If outdoor storage is unavoidable, lay drums horizontally to prevent water damage and label degradation.
- Store products in a temperature-controlled environment, avoiding temperatures above 60°C, direct sunlight, and freezing conditions.

## Health & Safety

The proper use of this product, in conjunction with adherence to good hygiene practices, is expected to minimize the risk of adverse health effects or safety hazards. It is essential to carefully follow the recommended application guidelines to ensure safe and effective use.

## Protect the environment

Used oil disposal instructions: Ensure environmentally responsible disposal by taking used oil to an authorized collection facility. Comply with all applicable local regulations and never discharge used oil into drains, soil, or waterways.