

Technical Data Sheet

G-CRANKS COMFORT 4T 15W-50

Product Description

G-CRANKZ COMFORT 4T 15W-50 is a high-performance Semi Synthetic engine oil that provides exceptional wear protection, designed for high-performance turbocharged 350cc engines and supercharged gasoline engines, it exceeds industry standards for high-performance fuel-injected engines. The product excels in a wide range of motorsports applications and other severe service applications. G-CRANKZ COMFORT 4T 15W-50 provides superior engine performance and engine protection.

Application



- It is recommended for all types of 350cc 4-stock motorcycles, suitable for use in high-performance turbo-charged, supercharged gasoline fuel-injected engines.
- This oil is best suited for extreme weather conditions, the city's "stop-n-go" conditions, and high-terrain rides.
- This oil is not recommended for 2-cycle or aviation engines unless specifically approved by the manufacturer.
- Suitable for water-cooled or air-cooled four-stroke engines.
- It is highly recommended for new and old generation heavy-duty 350cc engine leading manufacturers such as ROYAL ENFIELD, JAWA, YEZDI, HONDA, etc.

Key Performance Benefits

- Helps prevent deposits and sludge build-up to enable long engine life.
- It supports lowering emissions to permitted levels.
- Protects the engine from wear and tear, thus reducing maintenance costs.
- It keeps the engine clean for a trouble-free ride.
- This oil delivers higher clutch frictional performance.
- It keeps the engine cool under extreme weather conditions.

Performance Standards

- API SN
- JASO MA-2

GOHIL LUBRICANT PVT. LTD.

139, 1st Floor, Adarsh Industrial Estate, Andheri Sahar Road, Chakala, Andheri (E),
Mumbai - 400 099. For consumer complaints:
email: support@g-crankz.com Phone :- 180 0309 0302

Typical Characteristics

TYPICAL PROPERTIES	ASTM METHOD	TYPICAL VALUE
Appearance	VISUAL	Bright & Clear
Kinematic Viscosity @40°C, mm ² /s, cSt	ASTM D445	143.5
Kinematic Viscosity @100°C, mm ² /s, cSt	ASTM D445	19.1
Viscosity Index	ASTM D2270	152
Flash Point (COC), °C	ASTM D92	230
Pour Point, °C	ASTM D97	-36
Total Base Number, mg KOH/g	ISO 6619	7.0
Density @29.5°C, kg/m ³	ASTM D1298	0.875

Properties referred above are typical only and minor variations, which do not affect product performance, are expected to appear in standard manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade.

Storage

To ensure product quality and safety, follow these storage guidelines:

- Store packages under cover to protect from the elements.
- If outdoor storage is unavoidable, lay drums horizontally to prevent water damage and label degradation.
- Store products in a temperature-controlled environment, avoiding temperatures above 60°C, direct sunlight, and freezing conditions.

Health & Safety

The proper use of this product, in conjunction with adherence to good hygiene practices, is expected to minimize the risk of adverse health effects or safety hazards. It is essential to carefully follow the recommended application guidelines to ensure safe and effective use.

Protect the environment

Used oil disposal instructions: Ensure environmentally responsible disposal by taking used oil to an authorized collection facility. Comply with all applicable local regulations and never discharge used oil into drains, soil, or waterways.

GOHIL LUBRICANT PVT. LTD.

139, 1st Floor, Adarsh Industrial Estate, Andheri Sahar Road, Chakala, Andheri (E),
Mumbai - 400 099. For consumer complaints:
email: support@g-crankz.com Phone :- 180 0309 0302