

Technical Data Sheet

G-CRANKS 2T

Product Description

G-CRANKS 2T is a high-quality lubricant designed for 2-stroke vehicles and equipment. Its superior protection and compatibility make it an ideal choice for 2-stroke motorcycles, small engine equipment, ATVs, scooters, Rickshaw, motor boats, and lawn equipment

Performance Standards

- API TC
- JASO FC

GOHIL LUBRICANT PVT. LTD.

139, 1st Floor, Adarsh Industrial Estate, Andheri Sahar Road, Chakala, Andheri (E),
Mumbai - 400 099. For consumer complaints:
email: support@g-crankz.com Phone :- 180 0309 0302

A product by **GOHIL** |

Typical Characteristics

TYPICAL PROPERTIES	ASTM METHOD	TYPICAL VALUE
Appearance	VISUAL	Bright & Clear
Kinematic Viscosity @40°C, mm ² /s, cSt	ASTM D445	60.2
Kinematic Viscosity @100°C, mm ² /s, cSt	ASTM D445	5.1
Viscosity Index	ASTM D2270	144
Flash Point (COC), °C	ASTM D92	110
Pour Point, °C	ASTM D97	-42
Total Base Number, mg KOH/g	ISO 6619	2.0
Density @29.5°C, kg/m ³	ASTM D1298	0.848

Properties referred above are typical only and minor variations, which do not affect product performance, are expected to appear in standard manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade.

Storage

To ensure product quality and safety, follow these storage guidelines:

- Store packages under cover to protect from the elements.
- If outdoor storage is unavoidable, lay drums horizontally to prevent water damage and label degradation.
- Store products in a temperature-controlled environment, avoiding temperatures above 60°C, direct sunlight, and freezing conditions.

Health & Safety

The proper use of this product, in conjunction with adherence to good hygiene practices, is expected to minimize the risk of adverse health effects or safety hazards. It is essential to carefully follow the recommended application guidelines to ensure safe and effective use.

Protect the environment

Used oil disposal instructions: Ensure environmentally responsible disposal by taking used oil to an authorized collection facility. Comply with all applicable local regulations and never discharge used oil into drains, soil, or waterways.