

Technical Data Sheet

G-CRANKZ SUPER CNG 20W-50

Product Description

G-CRANKZ SUPER 20W-50 mineral engine oil is a super-quality product that offers excellent protection and performance. It is formulated with a tailor-made additive package to safeguard against wear, corrosion, and rust, ensuring optimal engine performance. This oil provides a long engine life for various vehicle types and ages, as well as enhanced protection across a wide temperature range.

Application



- It is advisable to use this product for all types of automobiles, including passenger cars and minivans, that run on CNG/LPG fuel. Additionally, best suitable for city ride vehicles such as Maruti ECCO, etc

Key Performance Benefits

- Ideal for a wide range of vehicles that require a high-quality product.
- Forms a thick oil coating that protects the engine from wear in all operating situations, resulting in a longer engine life.
- Utilizes modern detergent additives to prevent the formation of sludge and harmful deposits in the engine.
- Maintains the protective oil coating and viscosity grade throughout the drain interval.

Performance Standards

- API SL

GOHIL LUBRICANT PVT. LTD.

139, 1st Floor, Adarsh Industrial Estate, Andheri Sahar Road, Chakala, Andheri (E),
Mumbai - 400 099. For consumer complaints:
email: support@g-crankz.com Phone :- 180 0309 0302

Typical Characteristics

TYPICAL PROPERTIES	ASTM METHOD	TYPICAL VALUE
Appearance	VISUAL	Bright & Clear
Kinematic Viscosity @40°C, mm ² /s, cSt	ASTM D445	145.2
Kinematic Viscosity @100°C, mm ² /s, cSt	ASTM D445	18.5
Viscosity Index	ASTM D2270	143
Flash Point (COC), °C	ASTM D92	236
Pour Point, °C	ASTM D97	-24
Total Base Number, mg KOH/g	ISO 6619	5.0
Density @29.5°C, kg/m ³	ASTM D1298	0.875

Properties referred above are typical only and minor variations, which do not affect product performance, are expected to appear in standard manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade.

STORAGE

To ensure product quality and safety, follow these storage guidelines:

- Store packages under cover to protect from the elements.
- If outdoor storage is unavoidable, lay drums horizontally to prevent water damage and label degradation.
- Store products in a temperature-controlled environment, avoiding temperatures above 60°C, direct sunlight, and freezing conditions.

Health & Safety

The proper use of this product, in conjunction with adherence to good hygiene practices, is expected to minimize the risk of adverse health effects or safety hazards. It is essential to carefully follow the recommended application guidelines to ensure safe and effective use.

Protect the environment

Used oil disposal instructions: Ensure environmentally responsible disposal by taking used oil to an authorized collection facility. Comply with all applicable local regulations and never discharge used oil into drains, soil, or waterways.

GOHIL LUBRICANT PVT. LTD.

139, 1st Floor, Adarsh Industrial Estate, Andheri Sahar Road, Chakala, Andheri (E),
Mumbai - 400 099. For consumer complaints:
email: support@g-crankz.com Phone :- 180 0309 0302

A product by **GOHIL** |